

CloudEngine S5735-S-I Series Extended-Temperature Switches

CloudEngine S5735-S-I series extended-temperature switches have an industrial-grade operating temperature range as well as professional outdoor surge protection to withstand harsh outdoor cabinet environments. They can be widely used in scenarios such as Safe City and Ethernet to the x (ETTx).

Introduction


Huawei CloudEngine S5735-S-I series extended-temperature switches (S5735-S-I for short) are next-generation standard Layer 3 gigabit switches that provide flexible all-gigabit access and 10GE uplink ports.

Extended-temperature switches have an industrial-grade operating temperature range as well as professional outdoor surge protection to withstand harsh outdoor cabinet environments. As such, they can be widely used in access scenarios such as Safe City and Ethernet to the x (ETTx).

Product Overview


Models and Appearances

Models and appearances of the CloudEngine S5735-S-I series


Models and Appearances	Description
 <p>CloudEngine S5735-S24T4X-I</p>	<ul style="list-style-type: none"> • 24 x 10/100/1000Base-T Ethernet ports and 4 x 10GE SFP+ ports • 1+1 power supply backup • Forwarding performance: 95.2 Mpps • Switching capacity: 128 Gbps/336 Gbps

Power Supply

Technical specifications of the power supplies applicable to the CloudEngine S5735-S-I series

Power Module	Technical Specifications
 <p>PAC60S12-AR</p>	<ul style="list-style-type: none"> • Dimensions (H x W x D): 40 mm x 90 mm x 215 mm (1.6 in. x 3.5 in. x 8.5 in.) • Weight: 0.68 kg (1.5 lb) • Rated input voltage range: <ul style="list-style-type: none"> - 100 V AC to 240 V AC, 50/60 Hz - 240 V DC • Maximum input voltage range: <ul style="list-style-type: none"> - 90 V AC to 264 V AC, 47 Hz to 63 Hz - 190 V DC to 290 V DC

Power Module	Technical Specifications
	<ul style="list-style-type: none"> • Maximum input current: <ul style="list-style-type: none"> – 100 V AC to 240 V AC: 2 A – 240 V DC: 2 A • Maximum output current: 5 A • Maximum output power: 60 W • Hot swap: Supported

 <p>PDC180S12-CR</p>	<ul style="list-style-type: none"> • Dimensions (H x W x D): 40 mm x 90 mm x 215 mm (1.6 in. x 3.5 in. x 8.5 in.) • Weight: 0.62 kg (1.37 lb) • Rated input voltage range: -48 V DC to -60 V DC • Maximum input voltage range: -38.4 V DC to -72 V DC • Maximum input current: 6 A • Maximum output current: 15 A • Maximum output power: 180 W • Hot swap: Supported
---	---

Product Features and Highlights

Industrial-Grade Reliability, withstanding harsh outdoor environments

- Extended operating temperature range (- 40° C to +70° C), enabling it to work in harsh outdoor environments.

High-level integration and easy installation/deployment

- Supports Super Virtual Fabric (SVF) that virtualizes "Core/Aggregation + Access Switches" into a single logical device. The CloudEngine S5735-S-I can function as the SVF client. SVF provides the innovative network management solution in the industry, simplifies device management, and supports plug-and-play of devices, as well as supporting service configuration profiles. These profiles are configured on the core device and automatically delivered to access devices, implementing centralized control, simplifying service configuration, and enabling flexible configuration modification.
- Supports zero-touch provisioning (ZTP), USB-based deployment, configuration-free replacement of a faulty device, batch configuration, and batch remote upgrade. These functions facilitate device deployment, service provisioning, and other management and maintenance work, greatly reducing O&M costs. The switch can be managed and maintained using Simple Network Management Protocol (SNMP) v1, v2c, and v3, command line interface (CLI), web system, or Secure Shell (SSH) v2.0. Additionally, it supports remote network monitoring (RMON), multiple log hosts, interface traffic statistics collection, and network quality analysis that facilitates network optimization and reconstruction.

Professional video backhaul features

- Smart Fault Diagnosis (SFD) of the downstream IP cameras (IPCs): Specifically, the switch works with Huawei's network management system—eSight—to implement fast fault diagnosis based on the device management status, port status, and alarms of the network path on which the IPC resides, and quickly demarcate the type of fault that led to the IPC disconnection (for example, an IPC fault, network device fault, power failure, or optical fiber link fault). This capability improves O&M efficiency, reduces O&M costs, and increases the IPC connectivity rate.
- eMDI video quality demarcation: The switch works with Huawei eSight to analyze video service quality and quickly demarcate the video quality problem type, such as artifacts and frame freezing on the screen when playing a video.
- Mechanical lock and alarm reporting upon cover being opened: It can quickly detect damage and intrusion, ensuring device security.

Powerful Service Processing Capability and Multiple Security Control Mechanisms

- Various Layer 2 and Layer 3 multicast protocols, including Protocol Independent Multicast Sparse Mode (PIM SM), PIM Dense Mode (DM), PIM Source-Specific Multicast (SSM), Multicast Listener Discovery (MLD), and Internet Group Management Protocol (IGMP) snooping, ensuring high-quality HD video backhaul services.
- Layer 3 features, such as Open Shortest Path First (OSPF), Intermediate System to Intermediate System (IS-IS), Border Gateway Protocol (BGP), and Virtual Router Redundancy Protocol (VRRP), meeting enterprise access and aggregation service requirements and supporting more voice, video, and data applications.
- MAC address authentication, 802.1X authentication, Portal authentication, and dynamic delivery of user policies (VLAN, QoS, and ACL).
- Series of mechanisms to defend against DoS attacks and user-targeted attacks. DoS attacks are targeted at switches and include SYN flood, LAND, Smurf, and ICMP flood attacks. User-targeted attacks include bogus DHCP server attacks, IP/MAC address spoofing, DHCP request flood, and changing the DHCP CHADDR value.
- Setting up and maintaining a DHCP snooping binding table, and discarding the packets that do not match the table entries. DHCP snooping allows a physical port to be configured as a trusted or untrusted port to ensure that users are connected to only authorized DHCP servers.
- Strict ARP learning, protecting the network against ARP spoofing attacks and ensuring normal network access.

Multiple Reliability Mechanisms

- Huawei-developed Smart Ethernet Protection (SEP) technology and the latest Ethernet ring protection switching (ERPS) standard in addition to the traditional Spanning Tree Protocol (STP), Rapid Spanning Tree Protocol (RSTP), and Multiple Spanning Tree Protocol (MSTP). SEP is a ring protection protocol dedicated to the Ethernet link layer. It is applicable to various ring topologies such as open ring topology, closed ring topology, and cascading ring topology. SEP is reliable and easy to maintain, and implements fast protection switching (under 50 ms). ERPS is defined in ITU-T G.8032. It implements protection switching within milliseconds based on the traditional Ethernet MAC and bridging functions.
- Smart Link. One switch can be connected to multiple aggregation switches through multiple links to implement uplink backup, greatly improving the reliability of access devices.
- Ethernet OAM (IEEE 802.3ah/802.1ag), quickly detecting link faults.
- The all-in-one chassis supports current leakage protection, short-circuit protection, and automatic detection and recovery mechanisms. In the event of a short circuit, the CloudEngine S5735-S-I can automatically power off to protect its components. In addition, it supports the short circuit detection and protection function for connected terminals. Once the short circuit is recovered, the switch automatically resumes power supply. Moreover, the switch supports current leakage protection, and has passed the 700 V DC and 1200 V AC surge test before delivery to ensure device security.

Mature IPv6 Technologies

- The CloudEngine S5735-S-I series video backhaul switch uses the mature, stable VRP platform and supports IPv4/IPv6 dual stack, IPv6 RIPng, and IPv6 over IPv4 tunnels including manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels. With these IPv6 features, the switch can be deployed on IPv4-only networks, IPv6-only networks, or networks that run both IPv4 and IPv6, meeting the requirements for IPv4-to-IPv6 transition.

Intelligent Upgrade

- Switches support the intelligent upgrade feature. Specifically, switches obtain the version upgrade path and download the newest version for upgrade from the Huawei Online Upgrade Platform (HOUP). The entire upgrade process is highly automated and achieves one-click upgrade. In addition, preloading the version is supported, which greatly shortens the upgrade time and service interruption time.
- The intelligent upgrade feature greatly simplifies device upgrade operations and makes it possible for the customer to upgrade the version independently. This greatly reduces the customer's maintenance costs. In addition, the upgrade policies on the HOUP platform standardize the upgrade operations, which greatly reduces the risk of upgrade failures.

Cloud Management

- The Huawei cloud management platform allows users to configure, monitor, and inspect switches on the cloud, reducing on-site deployment and O&M manpower costs and decreasing network OPEX. Huawei switches support both cloud management and on-premise management modes. These two management modes can be flexibly switched as required to achieve smooth evolution while maximizing return on investment (ROI).

OPS

- CloudEngine S5735-S-I supports Open Programmability System (OPS), an open programmable system based on the Python language. IT administrators can program the O&M functions of a CloudEngine S5735-S-I switch through Python scripts to quickly innovate functions and implement intelligent O&M.

Licensing

CloudEngine S5735-S-I supports both the traditional feature-based licensing mode and the latest Huawei IDN One Software (N1 mode for short) licensing mode. The N1 mode is ideal for campus network deployments in enterprise private cloud mode, and greatly enhances the customer experiences in purchasing and upgrading software services with simplicity.

Software Package Features in N1 Mode

Switch Functions	N1 Basic Software	N1 Foundation Software Package	N1 Advanced Software Package
Basic network functions: Layer 2 functions, IPv4, IPv6, SVF, and others Note: For details, see the Functions and Features	√	√	√
Basic network automation based on the Agile Controller: <ul style="list-style-type: none"> Basic automation: Plug-and-play Basic monitoring: Application visualization NE management: Image and topology management and discovery 	×	√	√
Advanced network automation and intelligent O&M: VXLAN, user access authentication, free mobility, and CampusInsight basic functions	×	×	√

Note: Only V200R019C10 and later versions can support N1 mode

Product Specifications

Functions and Features

Function and Feature		Description	CloudEngine S5735-S-I Series switch
Ethernet features	Ethernet basics	Full-duplex, half-duplex, and auto-negotiation	Yes
		Rate auto-negotiation on an interface	Yes
		Auto MDI and MDI-X	Yes
		Flow control on an interface	Yes
		Jumbo frames	Yes
		Link aggregation	Yes
		Load balancing among links of a trunk	Yes
		Transparent transmission of Layer 2 protocol packets	Yes

Function and Feature		Description	CloudEngine S5735-S-I Series switch
		Device Link Detection Protocol (DLDP)	Yes
		Link Layer Discovery Protocol (LLDP)	Yes
		Link Layer Discovery Protocol-Media Endpoint Discovery (LLDP-MED)	Yes
		Interface isolation	Yes
		Broadcast traffic suppression on an interface	Yes
		Multicast traffic suppression on an interface	Yes
		Unknown unicast traffic suppression on an interface	Yes
		VLAN broadcast traffic suppression	Yes
		VLAN multicast traffic suppression	Yes
		VLAN unknown unicast traffic suppression	Yes
	VLAN	VLAN specification	4094
		VLANIF interface specification	1024
		Access mode	Yes
		Trunk mode	Yes
		Hybrid mode	Yes
		QinQ mode	Yes
		Default VLAN	Yes
		VLAN assignment based on interfaces	Yes
		VLAN assignment based on protocols	Yes
		VLAN assignment based on IP subnets	Yes
		VLAN assignment based on MAC addresses	Yes
		VLAN assignment based on MAC address + IP address	Yes
		VLAN assignment based on MAC address + IP address + interface number	Yes
		Adding double VLAN tags to packets based on interfaces	Yes
		VLAN mapping	Yes
		Selective QinQ	Yes
		MUX VLAN	Yes
		Voice VLAN	Yes
		Guest VLAN	Yes
		GVRP	GARP
	GVRP		Yes

Function and Feature		Description	CloudEngine S5735-S-I Series switch	
	VCMP	VCMP	Yes	
	MAC	MAC address	16512	
		Automatic learning of MAC addresses	Yes	
		Automatic aging of MAC addresses	Yes	
		Static, dynamic, and blackhole MAC address entries	Yes	
		Interface-based MAC address learning limiting	Yes	
		Sticky MAC	Yes	
		MAC address flapping detection	Yes	
		MAC address spoofing defense	Yes	
		Port bridge	Yes	
	ARP	Static ARP	Yes	
		Dynamic ARP	Yes	
		ARP entry	8180	
		ARP aging detection	Yes	
		Intra-VLAN proxy ARP	Yes	
		Routed proxy ARP	Yes	
	Ethernet loop protection	MSTP	STP	Yes
			RSTP	Yes
MSTP			Yes	
VBST			Yes	
BPDU protection			Yes	
Root protection			Yes	
Loop protection			Yes	
Defense against TC BPDU attacks			Yes	
Loopback detection		Loop detection on an interface	Yes	
SEP		SEP	Yes	
Smart Link		Smart Link	Yes	
		Smart Link multi-instance	Yes	
		Monitor Link	Yes	
RRPP		RRPP	Yes	
		Single RRPP ring	Yes	
		Tangent RRPP ring	Yes	
		Intersecting RRPP ring	Yes	

Function and Feature		Description	CloudEngine S5735-S-I Series switch	
	ERPS	Hybrid networking of RRPP rings and other ring networks	Yes	
		G.8032 v1	Yes	
		G.8032 v2	Yes	
		ERPS semi-ring topology	Yes	
		ERPS closed-ring topology	Yes	
IPv4/IPv6 forwarding	IPv4 and unicast routing	IPv4 static routing	Yes	
		VRF	Yes	
		DHCP client	Yes	
		DHCP server	Yes	
		DHCP relay	Yes	
		Routing policies	Yes	
		IPv4 routes	8192	
		RIPv1	Yes	
		RIPv2	Yes	
		OSPF	Yes	
		Policy-based routing (PBR)	Yes	
		Multicast routing features	IGMPv1/v2/v3	Yes
			PIM-DM	Yes
	PIM-SM		Yes	
	MSDP		Yes	
	IPv4 multicast routes		1500	
	IPv6 multicast routes		1500	
	Multicast routing policies		Yes	
	RPF		Yes	
	IPv6 features	IPv6 protocol stack	Yes	
		ND	Yes	
		ND entry	3072	
		ND snooping	Yes	
		DHCPv6 snooping	Yes	
		RIPng	Yes	
		DHCPv6 server	Yes	
		DHCPv6 relay	Yes	
		OSPFv3	Yes	

Function and Feature		Description	CloudEngine S5735-S-I Series switch
		IPv6 routes	3072
		VRRP6	Yes
		MLDv1/v2	Yes
		PIM-DM for IPv6	Yes
		PIM-SM for IPv6	Yes
Layer 2 multicast features	-	IGMPv1/v2/v3 snooping	Yes
		IGMP snooping proxy	Yes
		MLD snooping	Yes
		Multicast traffic suppression	Yes
		Inter-VLAN multicast replication	Yes
Device reliability	VRRP	VRRP standard protocol	Yes
Ethernet OAM	EFM (802.3ah)	Automatic discovery of links	Yes
		Link fault detection	Yes
		Link troubleshooting	Yes
		Remote loopback	Yes
	CFM (802.1ag)	Software-level CCM	Yes
		802.1ag MAC ping	Yes
		802.1ag MAC trace	Yes
	OAM association	Association between 802.1ag and 802.3ah	Yes
	Y.1731	Unidirectional delay and jitter measurement	Yes
		Bidirectional delay and jitter measurement	Yes
QoS features	Traffic classification	Traffic classification based on ACLs	Yes
		Configuring traffic classification priorities	Yes
		Matching the simple domains of packets	Yes
	Traffic behavior	Traffic filtering	Yes
		Traffic policing (CAR)	Yes
		Modifying the packet priorities	Yes
		Modifying the simple domains of packets	Yes
		Modifying the packet VLANs	Yes
	Traffic shaping	Traffic shaping on an egress interface	Yes
		Traffic shaping on queues on an interface	Yes
	Congestion avoidance	Tail drop	Yes
	Congestion	Priority Queuing (PQ)	Yes

Function and Feature		Description	CloudEngine S5735-S-I Series switch
	management	Weighted Deficit Round Robin (WDRR)	Yes
		PQ+WDRR	Yes
		Weighted Round Robin (WRR)	Yes
		PQ+WRR	Yes
ACL	Packet filtering at Layer 2 to Layer 4	Number of rules per IPv4 ACL	2048
		Number of rules per IPv6 ACL	2048
		Number of ACLv4	2816
		Basic IPv4 ACL	Yes
		Advanced IPv4 ACL	Yes
		Basic IPv6 ACL	Yes
		Advanced IPv6 ACL	Yes
		Layer 2 ACL	Yes
		User-defined ACL	Yes
Configuration and maintenance	Login and configuration management	Command line interface (CLI)-based configuration	Yes
		Console terminal service	Yes
		Telnet terminal service	Yes
		SSH v1.5	Yes
		SSH v2.0	Yes
		SNMP-based NMS for unified configuration	Yes
		Web page-based configuration and management	Yes
		EasyDeploy (client)	Yes
		SVF	Yes
		Cloud management	Yes
		OPS	Yes
	File system	Directory and file management	Yes
		File upload and download	Yes
	Monitoring and maintenance	eMDI	Yes
		Hardware monitoring	Yes
		Log information output	Yes
		Alarm information output	Yes
		Debugging information output	Yes
		Port mirroring	Yes
		Flow mirroring	Yes
Remote mirroring	Yes		

Function and Feature		Description	CloudEngine S5735-S-I Series switch
		Energy saving	Yes
	Version upgrade	Version upgrade	Yes
		Version rollback	Yes
Security	ARP security	ARP packet rate limiting	Yes
		ARP anti-spoofing	Yes
		Association between ARP and STP	Yes
		Dynamic ARP Inspection (DAI)	Yes
		Static ARP Inspection (SAI)	Yes
		Egress ARP Inspection (EAI)	Yes
	IP security	ICMP attack defense	Yes
		IPSG for IPv4	Yes
		IPSG user capacity	1024
		IPSG for IPv6	Yes
		IPSGv6 user capacity	512
	Local attack defense	CPU attack defense	Yes
	MFF	MFF	Yes
	DHCP snooping	DHCP snooping	Yes
		Option 82 function	Yes
		Dynamic rate limiting for DHCP packets	Yes
	Attack defense	Defense against malformed packet attacks	Yes
		Defense against UDP flood attacks	Yes
		Defense against TCP SYN flood attacks	Yes
		Defense against ICMP flood attacks	Yes
Defense against packet fragment attacks		Yes	
Local URPF		Yes	
User access and authentication	AAA	Local authentication	Yes
		Local authorization	Yes
		RADIUS authentication	Yes
		RADIUS authorization	Yes
		RADIUS accounting	Yes
		HWTACACS authentication	Yes
		HWTACACS authorization	Yes
		HWTACACS accounting	Yes

Function and Feature		Description	CloudEngine S5735-S-I Series switch
	NAC	802.1X authentication	Yes
		MAC address authentication	Yes
		Portal authentication	Yes
		Hybrid authentication	Yes
	Policy association	Functioning as the access device	Yes
Network management	-	Ping	Yes
		Tracert	Yes
		NQA	Yes
		NTP	Yes
		sFlow	Yes
		SNMP v1	Yes
		SNMP v2c	Yes
		SNMP v3	Yes
		HTTP	Yes
		HTTPS	Yes
		NETCONF/YANG	Yes
RMON	Yes		
Interoperability	-	VLAN-based Spanning Tree (VBST)	Yes
		Link-type Negotiation Protocol (LNP)	Yes
		VLAN Central Management Protocol (VCMP)	Yes

Hardware Specifications

Item		CloudEngine S5735-S24T4X-I
Physical specifications	Dimensions (H x W x D)	43.6 mm x 442.0 mm x 420.0 mm
	Chassis height	1 U
	Chassis weight (including packaging)	7.02 kg
Fixed port	GE port	24
	10GE port	4
Management port	ETH management port	Supported
	Console port (RJ45)	Supported
	USB port	USB 2.0
CPU	Frequency	1000 MHz
	Cores	4
Storage	Memory (RAM)	1 GB


Item		CloudEngine S5735-S24T4X-I
	Flash memory	Hardware: 512 MB, of which 306 MB is available for users
Power supply system	Power supply type	60 W AC 180 W DC
	Power supply redundancy	1+1 NOTE The backup power supply is optional.
	Rated voltage range	<ul style="list-style-type: none"> AC input: 100 V AC to 240 V AC, 50/60 Hz High-Voltage DC input: 240 V DC DC input: -48 V DC to -60 V DC
	Maximum voltage range	<ul style="list-style-type: none"> AC input: 90 V AC to 264 V AC, 47 Hz to 63 Hz High-Voltage DC input: 190 V DC to 290 V DC DC input: -38.4 V DC to -72 V DC
	Maximum input current	60 W AC: 2 A
	Maximum power consumption (100% throughput, full speed of fans)	55.2 W
	Typical power consumption (30% of traffic load) <ul style="list-style-type: none"> Tested according to ATIS standard EEE enabled 	36.8 W
	Minimum power consumption	23.7 W
Heat dissipation system	Heat dissipation mode	Heat dissipation with fan, intelligent fan speed adjustment
	Number of fan modules	3 built-in fans
	Airflow	Air intake from left, front and right, air exhaustion from behind
Environment parameters	Short-term operating temperature	<ul style="list-style-type: none"> 0-1800 m altitude: -40°C to +70°C NOTE When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.). The equipment can operate beyond the normal operating temperature range for a short-term period, but the following conditions must be met: <ul style="list-style-type: none"> The equipment operates at a temperature of over 65°C (149°F) consecutively for at most 96 hours in one year. The equipment operates at a temperature of over 65°C (149°F) for a total of no more than 360 hours in one year. The equipment operates at a temperature of over 65°C (149°F) for no more in 15 times in one year. The equipment may be damaged or experience unexpected exceptions if any of the preceding limits is exceeded. The maximum distance of optical modules used in these

Item		CloudEngine S5735-S24T4X-I
		conditions cannot exceed 10 km.
	Long-term operating temperature	<ul style="list-style-type: none"> 0-1800 m altitude: -40°C to +65°C NOTE When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.).
	Storage temperature	-40°C to +75°C
	Relative humidity	5% to 95% (non-condensing)
	Operating altitude	0-5000 m
	Noise under normal temperature (27°C, sound power)	< 49.5 dB(A)
	Service port surge protection	Common mode: ±7 kV
	Power supply surge protection	<ul style="list-style-type: none"> Using AC power modules: ±6 kV in differential mode, ±6 kV in common mode Using DC power modules: ±2 kV in differential mode, ±4 kV in common mode
Reliability	MTBF (year)	62.88
	MTTR (hour)	2
	Availability	> 0.99999
Certification		<ul style="list-style-type: none"> EMC certification Safety certification Manufacturing certification

Networking and Applications


Video backhaul application, outdoor cabinet

CloudEngine S5735-S-I series switches supports extended operating temperature range, with professional surge protection capabilities, suitable for outdoor cabinet environment. CloudEngine S5735-S-I series switch can be used for safe city scenario to provide remote access for the camera.



ETTx scenario

CloudEngine S5735-S-I series switches supports extended operating temperature and provides GE access and 10GE uplinks for ETTx access scenarios.



Safety and Regulatory Compliance

Certification Category	Description
Safety	<ul style="list-style-type: none"> • IEC 60950-1 • EN 60950-1/A11/A12 • UL 60950-1 • CSA C22.2 No 60950-1 • AS/NZS 60950.1 • CNS 14336-1 • IEC60825-1 • IEC60825-2 • EN60825-1 • EN60825-2
Electromagnetic Compatibility (EMC)	<ul style="list-style-type: none"> • CISPR22 Class A • CISPR24 • EN55022 Class A • EN55024 • ETSI EN 300 386 Class A • CFR 47 FCC Part 15 Class A • ICES 003 Class A • AS/NZS CISPR22 Class A • VCCI Class A • IEC61000-4-2 • ITU-T K 20 • ITU-T K 21 • ITU-T K 44

Certification Category	Description
	<ul style="list-style-type: none"> • CNS13438
Environment	<ul style="list-style-type: none"> • RoHS • REACH • WEEE

NOTE

- EMC: electromagnetic compatibility
- CISPR: International Special Committee on Radio Interference
- EN: European Standard
- ETSI: European Telecommunications Standards Institute
- CFR: Code of Federal Regulations
- FCC: Federal Communication Commission
- IEC: International Electrotechnical Commission
- AS/NZS: Australian/New Zealand Standard
- VCCI: Voluntary Control Council for Interference
- UL: Underwriters Laboratories
- CSA: Canadian Standards Association
- IEEE: Institute of Electrical and Electronics Engineers
- RoHS: restriction of the use of certain hazardous substances
- REACH: Registration Evaluation Authorization and Restriction of Chemicals
- WEEE: Waste Electrical and Electronic Equipment

MIB and Standards Compliance

Supported MIBs

Category	MIB
Public MIB	<ul style="list-style-type: none"> • BRIDGE-MIB • DISMAN-NSLOOKUP-MIB • DISMAN-PING-MIB • DISMAN-TRACEROUTE-MIB • ENTITY-MIB • EtherLike-MIB • IF-MIB • IP-FORWARD-MIB • IPv6-MIB • LAG-MIB • LLDP-EXT-DOT1-MIB • LLDP-EXT-DOT3-MIB • LLDP-MIB • NOTIFICATION-LOG-MIB • NQA-MIB • OSPF-TRAP-MIB • P-BRIDGE-MIB • Q-BRIDGE-MIB

Category	MIB
	<ul style="list-style-type: none"> • RFC1213-MIB • RIPv2-MIB • RMON-MIB • SAVI-MIB • SNMP-FRAMEWORK-MIB • SNMP-MPD-MIB • SNMP-NOTIFICATION-MIB • SNMP-TARGET-MIB • SNMP-USER-BASED-SM-MIB • SNMPv2-MIB • TCP-MIB • UDP-MIB
Huawei-proprietary MIB	<ul style="list-style-type: none"> • HUAWEI-AAA-MIB • HUAWEI-ACL-MIB • HUAWEI-ALARM-MIB • HUAWEI-ALARM-RELIABILITY-MIB • HUAWEI-BASE-TRAP-MIB • HUAWEI-BRAS-RADIUS-MIB • HUAWEI-BRAS-SRVCFG-EAP-MIB • HUAWEI-BRAS-SRVCFG-STATICUSER-MIB • HUAWEI-CBQOS-MIB • HUAWEI-CDP-COMPLIANCE-MIB • HUAWEI-CONFIG-MAN-MIB • HUAWEI-CPU-MIB • HUAWEI-DAD-TRAP-MIB • HUAWEI-DC-MIB • HUAWEI-DATASYNC-MIB • HUAWEI-DEVICE-MIB • HUAWEI-DHCPR-MIB • HUAWEI-DHCPS-MIB • HUAWEI-DHCP-SNOOPING-MIB • HUAWEI-DIE-MIB • HUAWEI-DNS-MIB • HUAWEI-DLDP-MIB • HUAWEI-ELMI-MIB • HUAWEI-ERPS-MIB • HUAWEI-ERRORDOWN-MIB • HUAWEI-ENERGYMNGT-MIB • HUAWEI-EASY-OPERATION-MIB • HUAWEI-ENTITY-EXTENT-MIB • HUAWEI-ENTITY-TRAP-MIB • HUAWEI-ETHARP-MIB • HUAWEI-ETHOAM-MIB • HUAWEI-FLASH-MAN-MIB

Category	MIB
	<ul style="list-style-type: none"> • HUAWEI-FWD-RES-TRAP-MIB • HUAWEI-GARP-APP-MIB • HUAWEI-GTSM-MIB • HUAWEI-HGMP-MIB • HUAWEI-HWTACACS-MIB • HUAWEI-IF-EXT-MIB • HUAWEI-INFOCENTER-MIB • HUAWEI-IPPOOL-MIB • HUAWEI-IPV6-MIB • HUAWEI-ISOLATE-MIB • HUAWEI-L2IF-MIB • HUAWEI-L2MAM-MIB • HUAWEI-L2VLAN-MIB • HUAWEI_LDT-MIB • HUAWEI-LLDP-MIB • HUAWEI-MAC-AUTHEN-MIB • HUAWEI-MEMORY-MIB • HUAWEI-MFF-MIB • HUAWEI-MFLP-MIB • HUAWEI-MSTP-MIB • HUAWEI-MULTICAST-MIB • HUAWEI-NAP-MIB • HUAWEI-NTPV3-MIB • HUAWEI-PERFORMANCE-MIB • HUAWEI-PORT-MIB • HUAWEI-PORTAL-MIB • HUAWEI-QINQ-MIB • HUAWEI-RIPv2-EXT-MIB • HUAWEI-RM-EXT-MIB • HUAWEI-RRPP-MIB • HUAWEI-SECURITY-MIB • HUAWEI-SEP-MIB • HUAWEI-SNMP-EXT-MIB • HUAWEI-SSH-MIB • HUAWEI-STACK-MIB • HUAWEI-SWITCH-L2MAM-EXT-MIB • HUAWEI-SWITCH-SRV-TRAP-MIB • HUAWEI-SYS-MAN-MIB • HUAWEI-TCP-MIB • HUAWEI-TFTPC-MIB • HUAWEI-TRNG-MIB • HUAWEI-XQOS-MIB

NOTE

For more detailed information of MIBs supported by the CloudEngine S5735-S series, visit <https://support.huawei.com/enterprise/en/switches/s5700-pid-6691579?category=reference-guides&subcategory=mib-reference>.

Standard Compliance

Standard Organization	Standard or Protocol
IETF	<ul style="list-style-type: none">• RFC 768 User Datagram Protocol (UDP)• RFC 792 Internet Control Message Protocol (ICMP)• RFC 793 Transmission Control Protocol (TCP)• RFC 826 Ethernet Address Resolution Protocol (ARP)• RFC 854 Telnet Protocol Specification• RFC 951 Bootstrap Protocol (BOOTP)• RFC 959 File Transfer Protocol (FTP)• RFC 1058 Routing Information Protocol (RIP)• RFC 1112 Host extensions for IP multicasting• RFC 1157 A Simple Network Management Protocol (SNMP)• RFC 1256 ICMP Router Discovery• RFC 1305 Network Time Protocol Version 3 (NTP)• RFC 1349 Internet Protocol (IP)• RFC 1493 Definitions of Managed Objects for Bridges• RFC 1542 Clarifications and Extensions for the Bootstrap Protocol• RFC 1643 Ethernet Interface MIB• RFC 1757 Remote Network Monitoring (RMON)• RFC 1901 Introduction to Community-based SNMPv2• RFC 1902-1907 SNMP v2• RFC 1981 Path MTU Discovery for IP version 6• RFC 2131 Dynamic Host Configuration Protocol (DHCP)• RFC 2328 OSPF Version 2• RFC 2453 RIP Version 2• RFC 2460 Internet Protocol, Version 6 Specification (IPv6)• RFC 2461 Neighbor Discovery for IP Version 6 (IPv6)• RFC 2462 IPv6 Stateless Address Auto configuration• RFC 2463 Internet Control Message Protocol for IPv6 (ICMPv6)• RFC 2474 Differentiated Services Field (DS Field)• RFC 2740 OSPF for IPv6 (OSPFv3)• RFC 2863 The Interfaces Group MIB• RFC 2597 Assured Forwarding PHB Group• RFC 2598 An Expedited Forwarding PHB• RFC 2571 SNMP Management Frameworks• RFC 2865 Remote Authentication Dial In User Service (RADIUS)• RFC 3046 DHCP Option82• RFC 3376 Internet Group Management Protocol, Version 3 (IGMPv3)• RFC 3513 IP Version 6 Addressing Architecture• RFC 3579 RADIUS Support For EAP• RFC 4271 A Border Gateway Protocol 4 (BGP-4)

Standard Organization	Standard or Protocol
	<ul style="list-style-type: none"> • RFC 4760 Multiprotocol Extensions for BGP-4 • draft-grant-tacacs-02 TACACS+
IEEE	<ul style="list-style-type: none"> • IEEE 802.1D Media Access Control (MAC) Bridges • IEEE 802.1p Traffic Class Expediting and Dynamic Multicast Filtering • IEEE 802.1Q Virtual Bridged Local Area Networks • IEEE 802.1ad Provider Bridges • IEEE 802.2 Logical Link Control • IEEE Std 802.3 CSMA/CD • IEEE Std 802.3ab 1000BASE-T specification • IEEE Std 802.3ad Aggregation of Multiple Link Segments • IEEE Std 802.3ae 10GE WEN/LAN Standard • IEEE Std 802.3x Full Duplex and flow control • IEEE Std 802.3z Gigabit Ethernet Standard • IEEE802.1ax/IEEE802.3ad Link Aggregation • IEEE 802.3ah Ethernet in the First Mile • IEEE 802.1ag Connectivity Fault Management • IEEE 802.1ab Link Layer Discovery Protocol • IEEE 802.1D Spanning Tree Protocol • IEEE 802.1w Rapid Spanning Tree Protocol • IEEE 802.1s Multiple Spanning Tree Protocol • IEEE 802.1x Port based network access control protocol • IEEE 802.3af DTE Power via MIDI • IEEE 802.3at DTE Power via the MDI Enhancements
ITU	<ul style="list-style-type: none"> • ITU SG13 Y.17ethoam • ITU SG13 QoS control Ethernet-Based IP Access • ITU-T Y.1731 ETH OAM performance monitor
ISO	<ul style="list-style-type: none"> • ISO 10589 IS-IS Routing Protocol
MEF	<ul style="list-style-type: none"> • MEF 2 Requirements and Framework for Ethernet Service Protection • MEF 9 Abstract Test Suite for Ethernet Services at the UNI • MEF 10.2 Ethernet Services Attributes Phase 2 • MEF 11 UNI Requirements and Framework • MEF 13 UNI Type 1 Implementation Agreement • MEF 15 Requirements for Management of Metro Ethernet Phase 1 Network Elements • MEF 17 Service OAM Framework and Requirements • MEF 20 UNI Type 2 Implementation Agreement • MEF 23 Class of Service Phase 1 Implementation Agreement • XMODEM/YMODEM Protocol Reference

Ordering Information

Module	Description
CloudEngine S5735-S24T4X-	CloudEngine S5735-S24T4X-I (24*10/100/1000BASE-T ports, 4*10GE SFP+ ports,

Module	Description
I	without power module)
PAC60S12-AR	60 W AC power module
PDC180S12-CR	180 W DC power module
N1-S57S-M-Lic	S57XX-S Series Basic SW,Per Device
N1-S57S-M-SnS1Y	S57XX-S Series Basic SW,SnS,Per Device,1Year
N1-S57S-F-Lic	N1-CloudCampus,Foundation,S57XX-S Series,Per Device
N1-S57S-F-SnS1Y	N1-CloudCampus,Foundation,S57XX-S Series,SnS,Per Device,1Year
N1-S57S-A-Lic	N1-CloudCampus,Advanced,S57XX-S Series,Per Device
N1-S57S-A-SnS1Y	N1-CloudCampus,Advanced,S57XX-S Series,SnS,Per Device,1Year
N1-S57S-FToA-Lic	N1-Upgrade-Foundation to Advanced,S57XX-S,Per Device
N1-S57S-FToA-SnS1Y	N1-Upgrade-Foundation to Advanced,S57XX-S,SnS,Per Device,1Year

More Information


For more information about Huawei Campus Switches, visit <http://e.huawei.com> or contact us in the following ways:

- Global service hotline: <http://e.huawei.com/en/service-hotline>
- Logging in to the Huawei Enterprise technical support website: <http://support.huawei.com/enterprise/>
- Sending an email to the customer service mailbox: support_e@huawei.com

Copyright © Huawei Technologies Co., Ltd. 2021. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address:Huawei Industrial Base Bantian,
Longgang Shenzhen 518129 People's
Republic of China

Website:e.huawei.com